



GREAT STUFF PRO™ WINDOW & DOOR INSULATING FOAM SEALANT

AN AIRTIGHT CASE



The average U.S. home has a half mile of gaps and cracks¹ where air and moisture can enter. Installing energy-efficient windows and doors can greatly reduce this infiltration, but another area is often overlooked - around the window and door frames. Uninsulated or underinsulated framework can contribute to the home's total energy loss and overall comfort.

Close the Gap

Seal out energy loss and help improve comfort by closing the gap between the framework and rough openings with GREAT STUFF PRO™ Window & Door Insulating Foam Sealant.

The low pressure-build formulation of GREAT STUFF PRO™ Window & Door Insulating Foam Sealant forms a durable, airtight and water-resistant seal between a window or door frame and its rough opening.

GREAT STUFF PRO™ Window & Door Insulating Foam Sealant is available in a 20 oz gun-applied version. The gun formulation can be used with the GREAT STUFF PRO™ Series Foam Dispensing Guns and is designed specifically for the PRO contractor.

With GREAT STUFF PRO™ Window & Door Insulating Foam Sealant, you can achieve better window or door installation. GREAT STUFF PRO™ Window & Door Insulating Foam Sealant helps to prevent drafts, repels water and more, resulting in higher quality installation, improved home comfort and greater customer satisfaction.

Features and Benefits At a Glance

- Meets ASTM E2112 standards
- Low pressure-build formulation at 0.13 psi; 0.90 kPa (average) (gun-applied foam) per AAMA 812-04
- When properly installed is proven not to bow or distort frame
- Expands to take the shape of gaps, creating a long-lasting, airtight and water-resistant seal
- Helps to maximize energy efficiency
- Bonds to vinyl, metal, wood and composite surfaces
- Repels and deflects water
- Tack-free in 3-10 minutes, Trims in 60 minutes²
- Fully cured in 8 hours
- UL classified
- One 20 oz. can (gun-applied) foams 16-18 average sized residential windows³



¹www.energystar.gov

² 70 ± 5 °F and 50 ± 5 %RH, 1 inch bead diameter, 6 inch length. Cure rate is dependent on temperature, humidity, and size of foam bead.

³ Based on average-sized windows 36" x 60", 3/8" wide gap, and 1" deep.

©™ Trademark of The Dow Chemical Company ("Dow") or an affiliated company of Dow

Where to Use GREAT STUFF PRO™ Window & Door Insulating Foam Sealant

Use GREAT STUFF PRO™ Window & Door Insulating Foam Sealant to seal around windows and doors and their rough openings.



Windows and their rough openings



Doors and their rough openings



When cured, remains soft and flexible. Cured foam can be stuffed back into the gap without trimming.

GREAT STUFF PRO™ Series Foam Dispensing Guns

GREAT STUFF PRO™ 13, 14, 15 Dispensing Guns

GREAT STUFF PRO™ 14XL Long Barrel Dispensing Gun

- Precision application
- High yield
- No drip dispensing
- 30 day restartability



Formulated for the Pros

Count on the GREAT STUFF PRO™ family of products to help you handle the toughest jobs.

- GREAT STUFF PRO™ Wall & Floor Adhesive
- GREAT STUFF PRO™ Gaps & Cracks Insulating Foam Sealant
- GREAT STUFF PRO™ Window & Door Insulating Foam Sealant
- GREAT STUFF PRO™ Pestblock Insulating Foam Sealant
- GREAT STUFF PRO™ Gun Cleaner



In the United States

The Dow Chemical Company Dow Building Solutions

200 Larkin Center
Midland, MI 48674

In Canada

The Dow Chemical Company Dow Building Solutions

2400, 215 – 2 Street S.W.,
Calgary, Alberta T2P 1M4

For Technical Information:

1-866-583-BLUE (2583) (English)
1-800-363-6210 (French)

dowgreatstuff.com

dowbuildingsolutions.com

For Sales Information:

1-800-232-2436 (English)
1-800-565-1255 (French)

NOTICE: No freedom from any patent owned by Dow or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where Dow is represented. The claims made may not have been approved for use in all countries or regions. Dow assumes no obligation or liability for the information in this document. References to "Dow" or the "Company" mean the Dow legal entity selling the products to Customer unless otherwise expressly noted. NO EXPRESS WARRANTIES ARE GIVEN EXCEPT FOR ANY APPLICABLE WRITTEN WARRANTIES SPECIFICALLY PROVIDED BY DOW. ALL IMPLIED WARRANTIES INCLUDING THOSE OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED. The buyer assumes all risks as to the use of the material. Buyer's exclusive remedy or any claim (including without limitations, negligence, strict liability, or tort) shall be limited to the refund of the purchase price of the material. Failure to strictly adhere to any recommended procedures shall release The Dow Chemical Company, and its subsidiaries, of all liability with respect to the materials or the use thereof. The information herein is not intended for use by non-professional designers, applicators or other persons who do not purchase or utilize this product in the normal course of their business.

Dow Polyurethane Foam Insulation and Sealants

CAUTION: When cured, these products are combustible and will burn if exposed to open flame or sparks from high-energy sources. Do not expose to temperatures above 240°F (116°C). For more information, consult (Material) Safety Data Sheet ((M)SDS), call Dow at 1-866-583-BLUE (2583) or contact your local building inspector. In an emergency, call 1-989-636-4400 in the U.S or 1-519-339-3711 in Canada. When air sealing buildings, ensure that combustion appliances, such as furnaces, water heaters, wood burning stoves, gas stoves and gas dryers are properly vented to the outside. See website: <http://www.epa.gov/iaq/homes/hip-ventilation.html>. In Canada visit <http://archive.nrc-cnrc.gc.ca/eng/ibp/irc/bsi/83-house-ventilation.html>

GREAT STUFF PRO™ sealant and adhesive products contain isocyanate and a flammable blowing agent. Read all instructions and (Material) Safety Data Sheet ((M)SDS), carefully before use. Eliminate all sources of ignition before use. Cover all skin. Wear long sleeves, gloves, and safety glasses or goggles. Not for use in aviation, or food/beverage contact, or as structural support in marine applications. Provide adequate ventilation or wear proper respiratory protection. Contents under pressure. Not to be used for filling closed cavities or voids such as behind walls and under tub surrounds; this improper use of the product could result in the accumulation of flammable vapors and/or uncured material. Failure to follow the warnings and instructions provided with the product, and/or all applicable rules and regulations, can result in injury or death.

GREAT STUFF PRO™ Gun Cleaner is flammable and contains acetone and propane. Read all instructions and (M)SDS carefully before use. Eliminate all sources of ignition before use. Cover all skin. Wear gloves, and goggles or safety glasses. Provide adequate ventilation or wear proper respiratory protection. Contents under pressure.

Building and/or construction practices unrelated to building materials could greatly affect moisture and the potential for mold formation. No material supplier including Dow can give assurance that mold will not develop in any specific system.

Printed in the U.S.A.

®/TM* Trademark of The Dow Chemical Company ("Dow") or an affiliated company of Dow

Form No. 179-07344-0317 CDP
178-00380-0317 CDP