

GREAT STUFF™

INSULATING FOAM SEALANT



NOW GREAT STUFF™ INSULATING FOAM IS EVEN GREATER!

Great Stuff™ Window & Door Insulating Foam Sealant

Features and Benefits:

- Fills, seals and insulates around windows and doors and their rough openings
- Use for up to 30 days with the Smart Dispenser™
- Forms a long-lasting weathertight seal to minimize drafts
- Repels/deflects water
- Enhances energy efficiency of the window or door installation
- Once cured, remains soft and flexible, allowing natural expansion and contraction between the frame and rough opening
- Tack free in 5-15 minutes²; trims in one hour
- Paintable, stainable and sandable
- Yellow colored foam
- All-direction dispensing
- UL Classified
- Conforms to ASTM & AAMA standards
- ESR-1961
- CCMC #13074-L
- One 12 oz. can foams 4-6 average sized residential windows (36" x 60", 3/8" wide gap, and 1" deep)

The average home has a half-mile of gaps and cracks¹ where air and moisture can enter. Installing energy-efficient windows and doors can greatly reduce air infiltration, but an area that is often overlooked is around windows and doors and their rough openings.

Seal out energy loss and improve comfort by sealing the gaps between framework and rough openings with Great Stuff™ Window & Door Insulating Foam Sealant.* This is a minimal-expanding polyurethane foam with low-pressure build that forms a durable, airtight and water-resistant seal between a window or door frame and its rough opening.

Introducing the new patent-pending Great Stuff™ Smart Dispenser™.

This next generation of foam sealant dispensing is a game-changer:

- Reusable for up to 30 days; now use it again and again!
- No drip dispensing, eliminates mess
- Easy to use, greater control
- Fill gaps efficiently and quickly
- Available only from Great Stuff™ Insulating Foams!

U.S. MADE



U.S. OWNED

GREAT STUFF™ SMART DISPENSER™
USE IT AGAIN AND AGAIN!



Where to Use Great Stuff™ Window & Door

Use Great Stuff™ Window & Door Insulating Foam Sealant to seal around windows and doors and their rough openings.



Doors and their rough openings



Windows and their rough openings



When cured, remains soft and flexible.
Cured foam can be stuffed back into the gap without trimming.



Meet the Great Stuff™ Foam Sealant Family:

Our line of foam sealants are a simple-to-use, cost-effective money-saving solution for any DIYer.

- **Great Stuff™ Gaps & Cracks*** — Fills, seals and insulates gaps up to 1 inch.
- **Great Stuff™ Window & Door*** — Seals airtight to insulate and reduce drafts, drip-free. When applied properly, won't distort or bow window and door frames.
- **Great Stuff™ Fireblock*** — Seals to impede fire and smoke with less mess.**
- **Great Stuff™ Big Gap Filler*** — Seals gaps up to 3 inches with less mess.
- **Great Stuff™ Pestblock*** — Blocks out ants, roaches, spiders, bees and more with no pesticides.
- **Great Stuff™ Multipurpose Black*** — Fills, seals and insulates indoor and outdoor gaps up to 1 inch.
- **Great Stuff™ Pond & Stone*** — Directs water flow with fish-safe adhesive and sealant.



¹ Source: www.energystar.gov

² 70 ± 5°F and 50 ± 5 % RH, 1 inch bead diameter, 6 inch length. Cure rate is dependent on temperature, humidity, and size of foam bead.

* Read all instructions and (Material) Safety Data Sheet ((M)SDS) carefully before use.

** Intended for use in residential application to maintain the continuity of an approved fire block material.

For more information visit us at greatstuff.com or call **1-866-583-2583**

NOTICE: No freedom from any patent owned by DuPont or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where DuPont is represented. The claims made may not have been approved for use in all countries or regions. DuPont assumes no obligation or liability for the information in this document. References to "DuPont" or the "Company" mean the DuPont legal entity selling the products to Customer unless otherwise expressly noted. NO EXPRESS WARRANTIES ARE GIVEN EXCEPT FOR ANY APPLICABLE WRITTEN WARRANTIES SPECIFICALLY PROVIDED BY DUPONT. ALL IMPLIED WARRANTIES INCLUDING THOSE OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED. The buyer assumes all risks as to the use of the material. Buyer's exclusive remedy or any claim (including without limitations, negligence, strict liability, or tort) shall be limited to the refund of the purchase price of the material. Failure to strictly adhere to any recommended procedures shall release DuPont Specialty Products USA, LLC or its affiliates, of all liability with respect to the materials or the use thereof. The information herein is not intended for use by non-professional designers, applicators or other persons who do not purchase or utilize this product in the normal course of their business.

DuPont Polyurethane Foam Insulation and Sealants

CAUTION: When cured, these products are combustible and will burn if exposed to open flame or sparks from high-energy sources. Do not expose to temperatures above 240°F (116°C). For more information, consult (Material) Safety Data Sheet ((M)SDS), call DuPont at 1-866-583-BLUE (2583) or contact your local building inspector. In an emergency, call 1-989-636-4400 in the U.S. or 1-519-339-3711 in Canada.

Great Stuff™ contains isocyanate and a flammable blowing agent. Read all instructions and (Material) Safety Data Sheet ((M)SDS), carefully before use. Eliminate all sources of ignition before use. Cover all skin. Wear long sleeves, gloves, and safety glasses or goggles. Not for use in aviation, or food/beverage contact, or as structural support in marine applications. Provide adequate ventilation or wear proper respiratory protection. Contents under pressure. Not to be used for filling closed cavities or voids such as behind walls and under tub surrounds; this improper use of the product could result in the accumulation of flammable vapors and/or uncured material. Failure to follow the warnings and instructions provided with the product, and/or all applicable rules and regulations, can result in injury or death.

Building and/or construction practices unrelated to building materials could greatly affect moisture and the potential for mold formation. No material supplier including DuPont can give assurance that mold will not develop in any specific system.

DuPont™, the DuPont Oval Logo, and all trademarks and service marks denoted with ™, ℠ or ® are owned by affiliates of DuPont de Nemours, Inc. unless otherwise noted. © 2019 DuPont.